

**Listing of Claims:**

1. (Currently Amended) An image processing system  
comprising:

an image capturing unit; and

an image processing unit,

5 the image capturing unit comprising:

an illuminating light source including a plurality of  
light-emitting devices which respectively emit illumination  
lights having a plurality of different characteristics of  
spectroscopic distributions;

10 an image pick-up optical system which forms an image of  
a subject illuminated by the illuminating light source;

an image pick-up device which picks up the subject  
image formed by the image pick-up optical system and obtains a  
subject signal; and

15 a control unit which controls light emission by the  
plurality of light-emitting devices and image pick-up by the  
image pick-up device and which switches the image capturing unit  
between a spectroscopic image capturing mode in which it obtains  
a still image of a subject spectroscopic image and a moving image  
20 capturing mode in which it obtains a moving image thereof;

wherein, in the spectroscopic image capturing mode, the  
control unit controls the plurality of light-emitting devices to

sequentially emit light according to the characteristics of spectroscopic distributions by a plurality of times interlocking the light emission with an exposure timing of the image pick-up device thereby causing the image pick-up device to obtain a plurality of subject spectroscopic images; and

wherein, in the moving image capturing mode, the control unit is arranged to (i) cause light emission of a light-emitting device for a single specific primary color or cause light emission of light-emitting devices for a plurality of specific primary colors selected from the plurality of light-emitting devices, or (ii) ~~cause simultaneous light emission of all of the plurality of light-emitting devices, or (iii)~~ cause sequential light emission of a group of R devices, a group of G devices, and a group of B devices selected from the plurality of light-emitting devices, group by group, and to cause the image pick-up device to obtain a moving image; and

the image processing unit comprising:

an image identification calculating unit which calculates grade data to be used to determine a grade of a color of the subject based on one or more of the subject spectroscopic images captured by the image capturing unit when operating in the spectroscopic image capturing mode.

Claims 2-16 (Canceled).

17. (Previously Presented) The image processing system according to claim 1, wherein the grade data indicates a grade of a shading guide for comparing the color of a tooth as the subject.

18. (Previously Presented) The image processing system according to claim 1, wherein the image processing unit calculates a ceramic compounding ratio of a false tooth based on the grade data to obtain false tooth ceramic compounding ratio data.

19. (Previously Presented) The image processing system according to claim 18, further comprising a computer connected to the image processing unit through a network, wherein the image processing unit transfers the grade data and the false tooth  
5 ceramic compounding ratio data to the computer.

20. (Previously Presented) The image processing system according to claim 19, further comprising a ceramic compounding ratio calculation database connected to the computer, wherein the computer searches for a ceramic compounding ratio from the  
5 ceramic compounding ratio calculation database based on the grade data and the false tooth ceramic compounding ratio data.

21. (Previously Presented) The image processing system according to claim 1, further comprising a display unit connected to the image processing unit, wherein the image identification calculating unit calculates the grade data before and after  
5 treatment of the subject, and the display unit displays the grade data calculated before and after the treatment of the subject.

22. (Previously Presented) The image processing system according to claim 1, wherein the image capturing unit further comprises an abutting portion formed in a cylindrical shape which abuts the subject.

23. (Previously Presented) The image processing system according to claim 22, wherein the abutting portion is configured to be detachably attached to the image capturing unit.

24. (Previously Presented) The image processing system according to claim 1, wherein the image capturing unit further comprises reflected light rejecting means for preventing the illuminating light source from being photographed to the subject.

25. (Previously Presented) The image processing system according to claim 1, wherein the image capturing unit further comprises an optical member which reduces the illuminating

unhomogeneity between the illuminating light source and the subject.

26. (Previously Presented) The image processing system according to claim 1, wherein the plurality of illuminating light sources include at least one of: (i) a light source with a center wavelength of 780 to 900 nm, and (ii) a light source with a center wavelength of 300 to 380 nm.

27. (Previously Presented) The image processing system according to claim 1, wherein the image capturing unit and the image processing unit are integrally formed.

28. (Previously Presented) The image processing system according to claim 1, wherein the image capturing unit includes a color chip for calibration in the image processing unit.

29. (Previously Presented) The image processing system according to claim 1, wherein the image capturing unit comprises a portable terminal device having a photographing function, and wherein an illuminating light source unit having the plurality of  
5 illuminating light sources as one unit is attachable to the portable terminal device.

30. (Previously Presented) The image processing system according to claim 1, wherein the image processing unit comprises image filing software, and image data photographed upon operating the photographing operating unit is recorded in accordance with the image filing software.

31. (Previously Presented) The image processing system according to claim 1, wherein the image capturing unit further comprises subject portion sensing means for obtaining positional information of the subject.

32. (Previously Presented) The image processing system according to claim 1, wherein the image capturing unit further comprises distance measuring means for managing a size of the subject in the photographed image.

33. (Previously Presented) The image processing system according to claim 32, wherein the image capturing unit further comprises a monitor which displays the image of the subject, and wherein the image capturing unit controls the monitor to display  
5 a difference between a photographing distance measured by the distance measuring means and a target photographing distance.

34. (Previously Presented) The image processing system according to claim 32, wherein the image capturing unit further comprises a monitor which displays the image of the subject, and wherein the image capturing unit controls the monitor to display  
5 an indication that the photographing distance measured by the distance measuring means matches a target photographing distance.

35. (Previously Presented) The image processing system according to claim 32, wherein the image capturing unit further comprises a monitor which displays the image of the subject, and wherein the image capturing unit obtains information of a desired  
5 photographing distance from images previously picked up, calculates a magnification correcting coefficient based on information of an actual photographing distance measured by the distance measuring means and the desired photographing distance information, and controls the monitor to display the image of the  
10 subject with a magnification corrected based on the magnification correcting coefficient.